


LORO-X COMPOSITE PIPE WITH 1 SOCKET

1500 MM DN 32

LORO-Composite Pipe 1.500 mm DN 32

Bestektekst

LORO-X compound pipe consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC free) and outer pipe (LORO-X pipe, made of steel, hot-dip galvanized), 1500 mm long, DN32



Artikelgegevens

EAN-code 4038088067802

ETIM Klasse EC010225

Nominale diameter DN 32

Nominale 1500

lengte/graad

Buitenafmetingen 89 x 89 x 1525 mm
(HxBxL)

Gewicht 7,50 Kg (STK)

Productgroep 3

Douanetariefnumme 73063012

r

Materiaal / Kleur Stahl feuerverzinkt, Silber

Gebruiksaanwijzing

Doppelwandiges Abflußrohr, DN 40 - DN 150 bestend aus: Innenrohr aus LORO-X Stahlabflußrohr, PU-Dämmschicht Baustoffklasse B2, FCKW-frei. Außenrohr aus LORO-X Stahlabflußrohr

Downloads



Alles online

[Installatiehandleiding \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[Maattekening \(PDF\)](#)

[CAD \(DWG\)](#)

[Brochure \(PDF\)](#)