
LORO-X COMPOSITE PIPE WITH 1 SOCKET 4000 MM DN 70

LORO-Composite Pipe 4000 mm DN 70

Beschrijving

LORO-X compound pipe consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC free) and outer pipe (LORO-X pipe, made of steel, hot-dip galvanized), 4000 mm long, DN70





Artikelgegevens

EAN-code	**4038088036181**
ETIM Klasse	**EC010225**
Nominale diameter	**DN 70**
Nominale lengte/graad	**4000**
Buitenafmetingen (HxBxL)	**102 x 102 x 4055 mm**
Gewicht	**35,50 Kg (STK)**
Productgroep	**3**
Douanetariefnummer	**73063012**
Materiaal / Kleur	**Stahl feuerverzinkt, Silber**

Gebruiksaanwijzing

Doppelwandiges Abflußrohr, DN 40 - DN 150 bestend aus: Innenrohr aus LORO-X Stahlabflußrohr, PU-Däammschicht Baustoffklasse B2, FCKW-frei. Außenrohr aus LORO-X Stahlabflußrohr

Downloads

Alles online

Installatiehandleiding (PDF)
CAD 2D (DXF)
BIM 3D (IFC)
Maattekening (PDF)
CAD 3D (DWG)
Brochure (PDF)
BIM 3D (STEP)