

LORO-X COMPOSITE PIPE WITH 1 SOCKET 4000 MM DN 125

LORO-Composite Pipe 4000 mm DN 125

Description

LORO-X compound pipe consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC free) and outer pipe (LORO-X pipe, made of steel, hot-dip galvanized), 4000 mm long, DN125




Article information

EAN Code	4038088036204
ETIM Class	EC010225
Nominal diameter	DN 125
Nominal length/degree	4000
Outside measurements (HxWxL)	168 x 168 x 4075 mm
Weight	95,00 Kg (STK)
Product group	3
Customs tariff number	73063018
Material / Color	Stahl feuerverzinkt, Silber

Usage note

Doppelwandiges Abflußrohr, DN 40 - DN 150 bestehend aus: Innenrohr aus LORO-X Stahlabflußrohr, PU-Dämmschicht Baustoffklasse B2, FCKW-frei. Außenrohr aus LORO-X Stahlabflußrohr



Downloads



Alles online

[Installation \(PDF\)](#)
[CAD 2D \(DXF\)](#)
[CAD drawing \(PDF\)](#)
[CAD \(DWG\)](#)
[Brochure \(PDF\)](#)