

LORO-X COMPOSITE PIPE WITH 1 SOCKET

4000 MM DN 125

LORO-Composite Pipe 4000 mm DN 125

Popis

LORO-X compound pipe consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC free) and outer pipe (LORO-X pipe, made of steel, hot-dip galvanized), 4000 mm long, DN125




Údaje o artiklu

EAN kód	4038088036204
ETIM třída	EC010225
Jmenovitý průměr	DN 125
Jmenovitá délka/stupeň	4000
Vnější rozměry (VxŠxD)	168 x 168 x 4075 mm
Hmotnost	95,00 Kg (STK)
Skupina produktů	3
Celní sazebník	73063018
Materiál / Barva	Stahl feuerverzinkt, Silber

Pokyny k použití

Doppelwandiges Abflußrohr, DN 40 - DN 150 bestehend aus: Innenrohr aus LORO-X Stahlabflußrohr, PU-Dämmschicht Baustoffklasse B2, FCKW-frei. Außenrohr aus LORO-X Stahlabflußrohr



Ke stažení



Alles online

[Návod k instalaci \(PDF\)](#)
[CAD 2D \(DXF\)](#)

[Výkres rozměrů \(PDF\)](#)
[CAD \(DWG\)](#)

[Prospekt \(PDF\)](#)