

## LORO-VERBUNDROHR-ABZW.87 GR. DN 40/40

LORO-Composite pipe branch 87 degrees DN 40/40

### Text pre výberové konanie

LORO-X compound pipe branch consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC free) and outer pipe (LORO-X pipe, made of steel, hot-dip galvanized), 87 degrees, DN40

### Údaje o artikli

|                           |                             |
|---------------------------|-----------------------------|
| EAN kód                   | 4038088090060               |
| ETIM trieda               | EC003025                    |
| Menovitý priemer          | DN 40, DN 40                |
| Menovitá dĺžka/stupeň     | 87                          |
| Vonkajšie rozmery (VxŠxH) | 135 x 89 x 168 mm           |
| Hmotnosť                  | 1,10 Kg (STK)               |
| Skupina produktov         | 3                           |
| Colný sadzobník           | 73089098                    |
| Materiál / Farba          | Stahl feuerverzinkt, Silber |

### Pokyny na použitie

Doppelwandiges Abflußrohr, DN 40 - DN 150 bestehend aus: Innenrohr aus LORO-X Stahlabflußrohr, PU-Dämmschicht Baustoffklasse B2, FCKW-frei. Außenrohr aus LORO-X Stahlabflußrohr

### Na stiahnutie



Alles online

[Návod na montáž \(PDF\)](#)

[Prospekt \(PDF\)](#)