LORO-VERBUNDROHR-ABZW.87 GR. DN 40/40

LORO-Composite pipe branch 87 degrees DN 40/40

Voce di capitolato

LORO-X compound pipe branch consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC free) and outer pipe (LORO-X pipe, made of steel, hot-dip galvanized), 87 degrees, DN40

Dati articolo

Codice EAN	**4038088090060**
Classe ETIM	**EC003025**
Diametro nominale	**DN 40, DN 40**
Lunghezza/grado nominale	**87**
Misure esterne (AxLxP)	**135 x 89 x 168 mm**
Peso	**1,10 Kg (STK)**
Gruppo prodotti	**3**
Numero tariffa doganale	**73089098**
Materiale / Colore	**Stahl feuerverzinkt, Silber**

Note d'uso

Doppelwandiges Abflußrohr, DN 40 - DN 150 bestend aus: Innenrohr aus LORO-X Stahlabflußrohr, PU-Däammschicht Baustoffklasse B2, FCKW-frei. Außenrohr aus LORO-X Stahlabflußrohr

Download

Istruzioni di installazione (PDF)

Brochure (PDF)

Alles online