

LORO-X COMPOSITE BRANCH 87 DEGREE

DN 50/50
LORO-Composite pipe branch 87 degrees DN 50/50

Leírás

LORO-X compound pipe branch consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC free) and outer pipe (LORO-X pipe, made of steel, hot-dip galvanized), 87 degrees, DN50




Cikkadatok

EAN kód	4038088024850
ETIM osztály	EC003025
Névleges átmérő	DN 50, DN 50
Névleges hossz/fok	87
Külső méretek (MxSzxH)	89 x 135 x 168 mm
Súly	1,30 Kg (STK)
Termékcsoport	3
Vámtarifaszám	73089098
Anyag / Szín	Stahl feuerverzinkt, Silber

Használati megjegyzés

Doppelwandiges Abflußrohr, DN 40 - DN 150 bestehend aus: Innenrohr aus LORO-X Stahlabflußrohr, PU-Dämmschicht Baustoffklasse B2, FCKW-frei. Außenrohr aus LORO-X Stahlabflußrohr



Letöltések



Alles online

[Szerelési útmutató \(PDF\)](#)
[CAD 2D \(DXF\)](#)
[Méterrajz \(PDF\)](#)
[CAD \(DWG\)](#)
[Prospektus \(PDF\)](#)