

## LORO-X COMPOSITE BRANCH 87 DEGREE

## DN 50/50

### LORO-Composite pipe branch 87 degrees DN 50/50

### Description

LORO-X compound pipe branch consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC free) and outer pipe (LORO-X pipe, made of steel, hot-dip galvanized), 87 degrees, DN50




## Données de l'article

|                                |                             |
|--------------------------------|-----------------------------|
| Code EAN                       | 4038088024850               |
| Classe ETIM                    | EC003025                    |
| Diamètre nominal               | DN 50, DN 50                |
| Longueur/degré nominal         | 87                          |
| Dimensions extérieures (HxLxP) | 89 x 135 x 168 mm           |
| Poids                          | 1,30 Kg (STK)               |
| Groupe de produits             | 3                           |
| Numéro tarifaire douanier      | 73089098                    |
| Matériau / Couleur             | Stahl feuerverzinkt, Silber |

## Note d'utilisation

Doppelwandiges Abflußrohr, DN 40 - DN 150 bestehend aus: Innenrohr aus LORO-X Stahlabflußrohr, PU-Dämmschicht Baustoffklasse B2, FCKW-frei. Außenrohr aus LORO-X Stahlabflußrohr



## Téléchargements



Alles online

[Notice d'installation \(PDF\)](#)

CAD 2D (DXF)

[Dessin dimensionnel \(PDF\)](#)

CAD (DWG)

[Brochure \(PDF\)](#)