


LORO-X COMPOSITE BRANCH 87 DEGREE

DN 125/125

LORO-Composite pipe branch 87 degrees DN 125/125

Beschrijving

LORO-X compound pipe branch consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC free) and outer pipe (LORO-X pipe, made of steel, hot-dip galvanized), 87 degrees, DN125



Artikelgegevens

EAN-code 4038088024881

ETIM Klasse EC003025

Nominale diameter DN 125, DN 125

Nominale lengte/graad 87

Buitenafmetingen (HxBxL) 168 x 283 x 360 mm

Gewicht 11,70 Kg (STK)

Productgroep 3

Douanetariefnummer 73089098

Materiaal / Kleur Stahl feuerverzinkt, Silber

Gebruiksaanwijzing

Doppelwandiges Abflußrohr, DN 40 - DN 150 bestehend aus: Innenrohr aus LORO-X Stahlabflußrohr, PU-Dämmschicht Baustoffklasse B2, FCKW-frei. Außenrohr aus LORO-X Stahlabflußrohr

Downloads



Alles online

[Installatiehandleiding \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[Maattekening \(PDF\)](#)

[CAD \(DWG\)](#)

[Brochure \(PDF\)](#)