


LORO-X COMPOSITE BRANCH 87 DEGREE

DN 150/150

LORO-Composite pipe branch 87 degrees DN 150/150

Opis

LORO-X compound pipe branch consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC free) and outer pipe (LORO-X pipe, made of steel, hot-dip galvanized), 87 degrees, DN150



Podatki o izdelku

EAN koda **4038088024898**

ETIM razred **EC003025**

Nazivni premer **DN 150, DN 150**

Nazivna
dolžina/stopinja **87**

Zunanje mere
(VxŠxD) **219 x 330 x 400 mm**

Teža **13,80 Kg (STK)**

Skupina izdelkov **3**

Carinska tarifna
številka **73089098**

Material / Barva **Stahl feuerverzinkt, Silber**

Opomba za uporabo

Doppelwandiges Abflußrohr, DN 40 - DN 150 bestehend aus: Innenrohr aus LORO-X Stahlabflußrohr, PU-Dämmschicht Baustoffklasse B2, FCKW-frei. Außenrohr aus LORO-X Stahlabflußrohr

Prenosi



Alles online

[Navodila za vgradnjo \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[Merska risba \(PDF\)](#)

[CAD \(DWG\)](#)

[Prospekt \(PDF\)](#)