

LORO-X COMPOSITE BRANCH 87 DEGREE

DN 150/150

LORO-Composite pipe branch 87 degrees DN 150/150

Descrição

LORO-X compound pipe branch consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC free) and outer pipe (LORO-X pipe, made of steel, hot-dip galvanized), 87 degrees, DN150



Dados do artigo

Código EAN 4038088024898

Classe ETIM EC003025

Diâmetro nominal DN 150, DN 150

Comprimento/grau nominal 87

Medidas exteriores (AxLxP) 219 x 330 x 400 mm

Peso 13,80 Kg (STK)


Grupo de produtos 3

Número de pauta aduaneira 73089098

Material / Cor Stahl feuerverzinkt, Silber

Nota de utilização

Doppelwandiges Abflußrohr, DN 40 - DN 150 bestehend aus: Innenrohr aus LORO-X Stahlabflußrohr, PU-Dämmschicht Baustoffklasse B2, FCKW-frei. Außenrohr aus LORO-X Stahlabflußrohr



Transferências



Alles online

[Instruções de instalação \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[Desenho cotado \(PDF\)](#)

[CAD \(DWG\)](#)

[Brochura \(PDF\)](#)