


LORO-X COMPOSITE BRANCH 87 DEGREE

DN 200/200

LORO-Composite pipe branch 87 degrees DN 200/200

Udbudstekst

LORO-X compound pipe branch consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC free) and outer pipe (LORO-X pipe, made of steel, hot-dip galvanized), 87 degrees, DN200



Artikeldata

EAN-kode	4038088038109
ETIM Klasse	EC003025
Nominel diameter	DN 200, DN 200
Nominel længde/grad	87
Ydermål (HxBxL)	273 x 433 x 540 mm
Vægt	36,60 Kg (STK)
Produktgruppe	3
Toldtarifnummer	73089098
Materiale / Farve	Stahl feuerverzinkt, Silber

Brugsanvisning

Doppelwandiges Abflußrohr, DN 40 - DN 150 bestehend aus: Innenrohr aus LORO-X Stahlabflußrohr, PU-Dämmschicht Baustoffklasse B2, FCKW-frei. Außenrohr aus LORO-X Stahlabflußrohr

Downloads



Alles online

[Installationsvejledning \(PDF\)](#)

CAD 2D (DXF)

[Måltegning \(PDF\)](#)

CAD (DWG)

[Brochure \(PDF\)](#)