

LORO-X COMPOSITE BRANCH 45 DEGREE

DN 40/40
LORO-Composite pipe branch 45 degrees DN 40/40

Περιγραφή

LORO-X compound pipe branch consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC free) and outer pipe (LORO-X pipe, made of steel, hot-dip galvanized), 45 degrees, DN40




Στοιχεία προϊόντος

Κωδικός EAN	4038088049815
Κατηγορία ETIM	EC003025
Ονομαστική διάμετρος	DN 40, DN 40
Ονομαστικό μήκος/μοίρες	45
Εξωτερικές διαστάσεις (ΥxΠxΜ)	89 x 182 x 198 mm
Βάρος	1,20 Kg (STK)
Ομάδα προϊόντων	3
Δασμολογικός αριθμός	73089098
Υλικό / Χρώμα	Stahl feuerverzinkt, Silber

Σημείωση χρήσης

Doppelwandiges Abflußrohr, DN 40 - DN 150 bestehend aus: Innenrohr aus LORO-X Stahlabflußrohr, PU-Dämmschicht Baustoffklasse B2, FCKW-frei. Außenrohr aus LORO-X Stahlabflußrohr



Λήψεις



Alles online

[Οδηγίες εγκατάστασης \(PDF\)](#)
[CAD 2D \(DXF\)](#)
[BIM 3D \(IFC\)](#)
[Σχέδιο διαστάσεων \(PDF\)](#)
[CAD 3D \(DWG\)](#)
[Φυλλάδιο \(PDF\)](#)
[BIM 3D \(STEP\)](#)