

LORO-X COMPOSITE BRANCH 45 DEGREE

DN 50/50
LORO-Composite pipe branch 45 degrees DN 50/50

Beskrivelse

LORO-X compound pipe branch consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC free) and outer pipe (LORO-X pipe, made of steel, hot-dip galvanized), 45 degrees, DN50




Artikeldata

EAN-kode	4038088024904
ETIM Klasse	EC003025
Nominal diameter	DN 50, DN 50
Nominal længde/grad	45
Ydermål (HxBxL)	89 x 166 x 188 mm
Vægt	1,60 Kg (STK)
Produktgruppe	3
Toldtarifnummer	73089098
Materiale / Farve	Stahl feuerverzinkt, Silber

Brugsanvisning

Doppelwandiges Abflußrohr, DN 40 - DN 150 bestend aus: Innenrohr aus LORO-X Stahlabflußrohr, PU-Dämmschicht Baustoffklasse B2, FCKW-frei. Außenrohr aus LORO-X Stahlabflußrohr



Downloads



Alles online

[Installationsvejledning \(PDF\)](#)
[CAD 2D \(DXF\)](#)
[Måltægning \(PDF\)](#)
[CAD \(DWG\)](#)
[Brochure \(PDF\)](#)