

LORO-X COMPOSITE BRANCH 45 DEGREE DN 70/70

LORO-Composite pipe branch 45 degrees DN 70/70

Opis

LORO-X compound pipe branch consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC free) and outer pipe (LORO-X pipe, made of steel, hot-dip galvanized), 45 degrees, DN70




Podaci o artiklu

EAN kod	4038088024911
ETIM klasa	EC003025
Nazivni promjer	DN 70, DN 70
Nazivna duljina/stupanj	45
Vanjske mjere (VxŠxD)	102 x 207 x 255 mm
Težina	2,70 Kg (STK)
Grupa proizvoda	3
Carinski tarifni broj	73089098
Materijal / Boja	Stahl feuerverzinkt, Silber

Napomena za upotrebu

Doppelwandiges Abflußrohr, DN 40 - DN 150 bestehend aus: Innenrohr aus LORO-X Stahlabflußrohr, PU-Dämmschicht Baustoffklasse B2, FCKW-frei. Außenrohr aus LORO-X Stahlabflußrohr



Preuzimanja



Alles online

[Upute za ugradnju \(PDF\)](#)

CAD 2D (DXF)

BIM 3D (IFC)

[Dimenzijski crtež \(PDF\)](#)

CAD 3D (DWG)

[Prospekt \(PDF\)](#)

BIM 3D (STEP)