

LORO-X COMPOSITE BRANCH 45 DEGREE

DN 32/32
LORO-Composite pipe branch 45 degrees DN 32/32

Tekst za troškovnik

LORO-X compound pipe branch consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC free) and outer pipe (LORO-X pipe, made of steel, hot-dip galvanized), 45 degrees, DN32



Podaci o artiklu

EAN kod	4038088086414
ETIM klasa	EC003025
Nazivni promjer	DN 32, DN 32
Nazivna duljina/stupanj	45
Vanjske mjere (VxŠxD)	89 x 182 x 198 mm
Težina	1,50 Kg (STK)
Grupa proizvoda	3
Carinski tarifni broj	73089098
Materijal / Boja	Stahl feuerverzinkt, Silber

Napomena za upotrebu

Doppelwandiges Abflußrohr, DN 40 - DN 150 bestehend aus: Innenrohr aus LORO-X Stahlabflußrohr, PU-Dämmschicht Baustoffklasse B2, FCKW-frei. Außenrohr aus LORO-X Stahlabflußrohr

Preuzimanja



Alles online

[Upute za ugradnju \(PDF\)](#)
[Prospekt \(PDF\)](#)