

LORO-X COMPOSITE BRANCH 45 DEGREE

DN 32/32

LORO-Composite pipe branch 45 degrees DN 32/32

Bestektekst

LORO-X compound pipe branch consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC free) and outer pipe (LORO-X pipe, made of steel, hot-dip galvanized), 45 degrees, DN32



Artikelgegevens

EAN-code	4038088086414
ETIM Klasse	EC003025
Nominale diameter	DN 32, DN 32
Nominale lengte/graad	45
Buitenafmetingen (HxBxL)	89 x 182 x 198 mm
Gewicht	1,50 Kg (STK)
Productgroep	3
Douanetariefnummer	73089098
Materiaal / Kleur	Stahl feuerverzinkt, Silber

Gebruiksaanwijzing

Doppelwandiges Abflußrohr, DN 40 - DN 150 bestend aus: Innenrohr aus LORO-X Stahlabflußrohr, PU-Dämmschicht Baustoffklasse B2, FCKW-frei. Außenrohr aus LORO-X Stahlabflußrohr

Downloads



Alles online

[Installatiehandleiding \(PDF\)](#)

[Brochure \(PDF\)](#)