# LORO-X COMPOSITE BRANCH 45 DEGREE DN 32/32

**LORO-Composite pipe branch 45 degrees DN 32/32**

## Tekst przetargowy

LORO-X compound pipe branch consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC free) and outer pipe (LORO-X pipe, made of steel, hot-dip galvanized), 45 degrees, DN32

## Dane artykułu

| | |
|---|---|
| Kod EAN | 4038088086414 |
| Klasa ETIM | EC003025 |
| Średnica nominalna | DN 32, DN 32 |
| Długość/stopień nominalny | 45 |
| Wymiary zewnętrzne (WxSxD) | 89 x 182 x 198 mm |
| Waga | 1,50 Kg (STK) |
| Grupa produktów | 3 |
| Numer taryfy celnej | 73089098 |
| Materiał / Kolor | Stahl feuerverzinkt, Silber |

## Wskazówki dotyczące użytkowania

Doppelwandiges Abflußrohr, DN 40 - DN 150 bestend aus: Innenrohr aus LORO-X Stahlabflußrohr, PU-Däammschicht Baustoffklasse B2, FCKW-frei. Außenrohr aus LORO-X Stahlabflußrohr

## Pobieranie

Instrukcja montażu (PDF)

Broszura (PDF)

Alles online