

LORO-X COMPOSITE REDUCED BRANCH 87 DEGREE DN 70/50

LORO-Composite Pipe Red. branch 87 degrees DN 70/50

Beskrivelse

LORO-X compound pipe reducing branch consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized), 87 degrees, DN70/50




Artikkeldata

EAN-kode	4038088024959
ETIM-klasse	EC003025
Nominell diameter	DN 70, DN 50
Nominell lengde/grad	87
Utvendige mål (HxBxL)	102 x 152 x 205 mm
Vekt	3,00 Kg (STK)
Produktgruppe	3
Tolltariffnummer	73089098
Materiale / Farge	Stahl feuerverzinkt, Silber

Bruksanvisning

Doppelwandiges Abflußrohr, DN 40 - DN 150 bestehend aus: Innenrohr aus LORO-X Stahlabflußrohr, PU-Dämmschicht Baustoffklasse B2, FCKW-frei. Außenrohr aus LORO-X Stahlabflußrohr



Nedlastinger



Alles online

[Monteringsanvisning \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[BIM 3D \(IFC\)](#)

[Måltegning \(PDF\)](#)

[CAD 3D \(DWG\)](#)

[Brosjyre \(PDF\)](#)

[BIM 3D \(STEP\)](#)