

LORO-X COMPOSITE REDUCED BRANCH 88 DEGREE DN 100/50

LORO-Composite Pipe Red. branch 87 degrees DN 100/50

Descripción

LORO-X compound pipe reducing branch consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized), 87 degrees, DN100/50




Datos del artículo

Código EAN	4038088024966
Clase ETIM	EC003025
Diámetro nominal	DN 100, DN 50
Longitud/grado nominal	88
Medidas exteriores (AxAxL)	133 x 194 x 260 mm
Peso	3,60 Kg (STK)
Grupo de productos	3
Número de arancel aduanero	73089098
Material / Color	Stahl feuerverzinkt, Silber

Nota de uso

Doppelwandiges Abflußrohr, DN 40 - DN 150 bestehend aus: Innenrohr aus LORO-X Stahlabflußrohr, PU-Dämmschicht Baustoffklasse B2, FCKW-frei. Außenrohr aus LORO-X Stahlabflußrohr



Descargas



Alles online

[Instrucciones de instalación \(PDF\)](#)
[CAD 2D \(DXF\)](#)

[Dibujo dimensional \(PDF\)](#)
[CAD \(DWG\)](#)

[Folleto \(PDF\)](#)