


LORO-X COMPOSITE REDUCED BRANCH 88 DEGREE DN 125/100

LORO-Composite Pipe Red. branch 87 degrees DN 125/100

Beschrijving

LORO-X compound pipe reducing branch consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized), 87 degrees, DN125/100



Artikelgegevens

EAN-code 4038088024980

ETIM Klasse EC003025

Nominale diameter DN 125, DN 100

Nominale lengte/graad 88

Buitenafmetingen (HxBxL) 168 x 262 x 330 mm

Gewicht 7,70 Kg (STK)

Productgroep 3

Douanetariefnumme r 73089098

Materiaal / Kleur Stahl feuerverzinkt, Silber

Gebruiksaanwijzing

Doppelwandiges Abflußrohr, DN 40 - DN 150 bestehend aus: Innenrohr aus LORO-X Stahlabflußrohr, PU-Dämmschicht Baustoffklasse B2, FCKW-frei. Außenrohr aus LORO-X Stahlabflußrohr

Downloads



Alles online

[Installatiehandleiding \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[Maattekening \(PDF\)](#)

[CAD \(DWG\)](#)

[Brochure \(PDF\)](#)