

## LORO-X COMPOSITE REDUCED BRANCH 88 DEGREE DN 150/100

LORO-Composite Pipe Red. branch 87 degrees DN 150/100

### Opis

LORO-X compound pipe reducing branch consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized), 87 degrees, DN150/100




### Podatki o izdelku

|                           |                             |
|---------------------------|-----------------------------|
| EAN koda                  | 4038088038123               |
| ETIM razred               | EC003025                    |
| Nazivni premer            | DN 150, DN 100              |
| Nazivna dolžina/stopinja  | 88                          |
| Zunanje mere (VxŠxD)      | 219 x 302 x 335 mm          |
| Teža                      | 9,80 Kg (STK)               |
| Skupina izdelkov          | 3                           |
| Carinska tarifna številka | 73089098                    |
| Material / Barva          | Stahl feuerverzinkt, Silber |

### Opomba za uporabo

Doppelwandiges Abflußrohr, DN 40 - DN 150 bestehend aus: Innenrohr aus LORO-X Stahlabflußrohr, PU-Dämmschicht Baustoffklasse B2, FCKW-frei. Außenrohr aus LORO-X Stahlabflußrohr



### Prenosi



Alles online

[Navodila za vgradnjo \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[Merska risba \(PDF\)](#)

[CAD \(DWG\)](#)

[Prospekt \(PDF\)](#)