

## LORO-X COMPOSITE REDUCED BRANCH 88 DEGREE DN 150/125

### LORO-Composite Pipe Red. branch 87 degrees DN 150/125

#### Kuvaus

LORO-X compound pipe reducing branch consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized), 87 degrees, DN150/125




#### Tuotetiedot

|                       |                             |
|-----------------------|-----------------------------|
| EAN-koodi             | 4038088038130               |
| ETIM-luokka           | EC003025                    |
| Nimellishalkaisija    | DN 150, DN 125              |
| Nimellispuiteus/-aste | 88                          |
| Ulkomitat (KxLxS)     | 219 x 323 x 370 mm          |
| Paino                 | 11,00 Kg (STK)              |
| Tuoteryhmä            | 3                           |
| Tullitariffin numero  | 73089098                    |
| Materiaali / Väri     | Stahl feuerverzinkt, Silber |

#### Käyttöohje

Doppelwandiges Abflußrohr, DN 40 - DN 150 bestehend aus: Innenrohr aus LORO-X Stahlabflußrohr, PU-Dämmschicht Baustoffklasse B2, FCKW-frei. Außenrohr aus LORO-X Stahlabflußrohr



#### Lataukset



Alles online

[Asennusohje \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[Mittapiirustus \(PDF\)](#)

[CAD \(DWG\)](#)

[Esite \(PDF\)](#)