

LORO-X COMPOSITE REDUCED BRANCH 45 DEGREE DN 50/40

LORO-Composite Pipe Red.-branch 45 degrees DN 50/40

Opis

LORO-X compound pipe reducing branch consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized), 45 degrees, DN50/40




Podatki o izdelku

EAN koda	4038088049839
ETIM razred	EC003025
Nazivni premer	DN 50, DN 40
Nazivna dolžina/stopinja	45
Zunanje mere (VxŠxD)	89 x 198 x 227 mm
Teža	1,50 Kg (STK)
Skupina izdelkov	3
Carinska tarifna številka	73089098
Material / Barva	Stahl feuerverzinkt, Silber

Opomba za uporabo

Doppelwandiges Abflußrohr, DN 40 - DN 150 bestehend aus: Innenrohr aus LORO-X Stahlabflußrohr, PU-Dämmschicht Baustoffklasse B2, FCKW-frei. Außenrohr aus LORO-X Stahlabflußrohr



Prenosi



Alles online

[Navodila za vgradnjo \(PDF\)](#)
[CAD 2D \(DXF\)](#)

[Merska risba \(PDF\)](#)
[CAD \(DWG\)](#)

[Prospekt \(PDF\)](#)