

## LORO-VERBUND-RED.-ABZW. 45GR. DN 50/ 32

LORO-Composite pipe Red. branch 45 degrees DN 50/ 32

### Voce di capitolato

LORO-X compound pipe reducing branch consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized), 45 degrees, DN50/32




### Dati articolo

|                          |                             |
|--------------------------|-----------------------------|
| Codice EAN               | 4038088067284               |
| Classe ETIM              | EC003025                    |
| Diametro nominale        | DN 50, DN 32                |
| Lunghezza/grado nominale | 45                          |
| Peso                     | 1,60 Kg (STK)               |
| Gruppo prodotti          | 3                           |
| Numero tariffa doganale  | 73089098                    |
| Materiale / Colore       | Stahl feuerverzinkt, Silber |

### Note d'uso

Doppelwandiges Abflußrohr, DN 40 - DN 150 bestehend aus: Innenrohr aus LORO-X Stahlabflußrohr, PU-Dämmschicht Baustoffklasse B2, FCKW-frei. Außenrohr aus LORO-X Stahlabflußrohr



### Download



Alles online

[Istruzioni di installazione \(PDF\)](#)  
[CAD 2D \(DXF\)](#)

[Disegno dimensionale \(PDF\)](#)  
[CAD \(DWG\)](#)

[Brochure \(PDF\)](#)