


LORO-X COMPOSITE REDUCED BRANCH 45 DEGREE DN 100/40

LORO-Composite Pipe Red. branch

Bestektekst

LORO-X compound pipe reducing branch consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized), 45 degrees, DN100/40



Artikelgegevens

EAN-code	4038088049877
ETIM Klasse	EC003025
Nominale diameter	DN 100, DN 40
Nominale lengte/graad	45
Gewicht	6,00 Kg (STK)
Productgroep	3
Douanetariefnummer	73089098

Materiaal / Kleur	Stahl feuerverzinkt, Silber
--------------------------	------------------------------------

Gebruiksaanwijzing

Doppelwandiges Abflußrohr, DN 40 - DN 150 bestehend aus: Innenrohr aus LORO-X Stahlabflußrohr, PU-Dämmschicht Baustoffklasse B2, FCKW-frei. Außenrohr aus LORO-X Stahlabflußrohr

Downloads



Alles online

[Installatiehandleiding \(PDF\)](#)

CAD 2D (DXF)

BIM IFC4 (parametrisch)

[Maattekening \(PDF\)](#)

CAD 3D (DWG)

BIM 3D (IFC)

[Brochure \(PDF\)](#)

BIM 3D (STEP)

5th of October