

LORO-X COMPOSITE REDUCED BRANCH 45 DEGREE DN 100/50

LORO-Composite Pipe Red. branch 45 degrees DN 100/50

Leírás

LORO-X compound pipe reducing branch consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized), 45 degrees, DN100/50




Cikkadatok

EAN kód	4038088025000
ETIM osztály	EC003025
Névleges átmérő	DN 100, DN 50
Névleges hossz/fok	45
Külső méretek (MxSzxH)	133 x 215 x 270 mm
Súly	3,90 Kg (STK)
Termékcsoport	3
Vámtarifaszám	73089098
Anyag / Szín	Stahl feuerverzinkt, Silber

Használati megjegyzés

Doppelwandiges Abflußrohr, DN 40 - DN 150 bestehend aus: Innenrohr aus LORO-X Stahlabflußrohr, PU-Dämmschicht Baustoffklasse B2, FCKW-frei. Außenrohr aus LORO-X Stahlabflußrohr



Letöltések



Alles online

[Szerelési útmutató \(PDF\)](#)
[CAD 2D \(DXF\)](#)

[Méterrajz \(PDF\)](#)
[CAD \(DWG\)](#)

[Prospektus \(PDF\)](#)