

## LORO-X COMPOSITE REDUCED BRANCH 45 DEGREE DN 100/80

### LORO-Composite Pipe Red. branch

#### Kiírási szöveg

LORO-X compound pipe reducing branch consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized), 45 degrees, DN100/80



#### Cikkadatok

|                        |                             |
|------------------------|-----------------------------|
| EAN kód                | 4038088049884               |
| ETIM osztály           | EC003025                    |
| Névleges átmérő        | DN 100, DN 80               |
| Névleges hossz/fok     | 45                          |
| Külső méretek (MxSzxH) | 133 x 287 x 320 mm          |
| Súly                   | 6,80 Kg (STK)               |
| Termékcsoport          | 3                           |
| Vámtarifaszám          | 73089098                    |
| Anyag / Szín           | Stahl feuerverzinkt, Silber |

#### Használati megjegyzés

Doppelwandiges Abflußrohr, DN 40 - DN 150 bestend aus: Innenrohr aus LORO-X Stahlabflußrohr, PU-Dämmschicht Baustoffklasse B2, FCKW-frei. Außenrohr aus LORO-X Stahlabflußrohr

#### Letöltések



Alles online

[Szerelési útmutató \(PDF\)](#)

[Prospektus \(PDF\)](#)

[BIM IFC4 \(parametrisch\)](#)