

LORO-X COMPOSITE REDUCED BRANCH 45 DEGREE DN 100/80

LORO-Composite Pipe Red. branch

Voce di capitolato

LORO-X compound pipe reducing branch consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized), 45 degrees, DN100/80



Dati articolo

Codice EAN	4038088049884
Classe ETIM	EC003025
Diametro nominale	DN 100, DN 80
Lunghezza/grado nominale	45
Misure esterne (AxLxP)	133 x 287 x 320 mm
Peso	6,80 Kg (STK)
Gruppo prodotti	3
Numero tariffa doganale	73089098
Materiale / Colore	Stahl feuerverzinkt, Silber

Note d'uso

Doppelwandiges Abflußrohr, DN 40 - DN 150 bestehend aus: Innenrohr aus LORO-X Stahlabflußrohr, PU-Dämmschicht Baustoffklasse B2, FCKW-frei. Außenrohr aus LORO-X Stahlabflußrohr

Download



Alles online

[Istruzioni di installazione \(PDF\)](#)

[Brochure \(PDF\)](#)

[BIM IFC4 \(parametric\)](#)