LORO-X COMPOSITE REDUCED BRANCH 45 DEGREE DN 100/80

LORO-Composite Pipe Red. branch

Beskrivelsestekst

LORO-X compound pipe reducing branch consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized), 45 degrees, DN100/80

Artikkeldata

EAN-kode	4038088049884
ETIM-klasse	EC003025
Nominell diameter	DN 100, DN 80
Nominell lengde/grad	45
Utvendige mål (HxBxL)	133 x 287 x 320 mm
Vekt	6,80 Kg (STK)
Produktgruppe	3
Tolltariffnummer	73089098
Materiale / Farge	Stahl feuerverzinkt, Silber

Bruksanvisning

Doppelwandiges Abflußrohr, DN 40 - DN 150 bestend aus: Innenrohr aus LORO-X Stahlabflußrohr, PU-Däammschicht Baustoffklasse B2, FCKW-frei. Außenrohr aus LORO-X Stahlabflußrohr

Nedlastinger

Monteringsanvisning (PDF) Brosjyre (PDF) BIM IFC4 (parametrisch)

Alles online