LORO-X COMPOSITE REDUCED BRANCH 45 DEGREE DN 125/50

LORO-Composite Pipe Red. branch

Texto para caderno de encargos

LORO-X compound pipe reducing branch consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized), 45 degrees, DN125/50

Dados do artigo

Código EAN	**4038088049891**
Classe ETIM	**EC003025**
Diâmetro nominal	**DN 125, DN 50**
Comprimento/grau nominal	**45**
Medidas exteriores (AxLxP)	**168 x 268 x 300 mm**
Peso	**9,50 Kg (STK)**
Grupo de produtos	**3**
Número de pauta aduaneira	**73089098**
Material / Cor	**Stahl feuerverzinkt, Silber**

Nota de utilização

Doppelwandiges Abflußrohr, DN 40 - DN 150 bestend aus: Innenrohr aus LORO-X Stahlabflußrohr, PU-Däammschicht Baustoffklasse B2, FCKW-frei. Außenrohr aus LORO-X Stahlabflußrohr

Transferências

Instruções de instalação (PDF) Brochura (PDF) BIM IFC4 (parametrisch)

Alles online