LORO-VERBUNDROHR-RED.-ABZWEIG

LORO-Composite Pipe Red.-branch

Text pro výběrové řízení

LORO-X compound pipe reducing branch consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized), 45 degrees, DN 80/50



Údaje o artiklu

EAN kód	**4038088049853**
ETIM třída	**EC003025**
Jmenovitý průměr	**DN 80, DN 50**
Jmenovitá délka/stupeň	**45**
Vnější rozměry (VxŠxD)	**219 x 229 x 245 mm**
Hmotnost	**4,50 Kg (STK)**
Skupina produktů	**3**
Celní sazebník	**73089098**
Materiál / Barva	**Stahl feuerverzinkt, Silber**

Pokyny k použití

Doppelwandiges Abflußrohr, DN 40 - DN 150 bestend aus: Innenrohr aus LORO-X Stahlabflußrohr, PU-Däammschicht Baustoffklasse B2, FCKW-frei. Außenrohr aus LORO-X Stahlabflußrohr

Ke stažení

Alles online

Návod k instalaci (PDF)
Výkres rozměrů (PDF)
Prospekt (PDF)
CAD 2D (DXF)
CAD (DWG)
BIM IFC4 (parametrisch)