# LORO-X COMPOSITE BEND 87 DEGREE DN 32

**LORO-Composite Pipe Bend 87 degrees DN 32**

## Κείμενο προδιαγραφών

LORO-X compound pipe bend consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized), 87 degrees, DN32

## Στοιχεία προϊόντος

| | |
|---|---|
| Κωδικός EAN | **4038088072158** |
| Κατηγορία ETIM | **EC003024** |
| Ονομαστική διάμετρος | **DN 32** |
| Ονομαστικό μήκος/μοίρες | **87** |
| Εξωτερικές διαστάσεις (ΥxΠxΜ) | **89 x 142 x 149 mm** |
| Βάρος | **0,80 Kg (STK)** |
| Ομάδα προϊόντων | **3** |
| Δασμολογικός αριθμός | **73089098** |
| Υλικό / Χρώμα | **Stahl feuerverzinkt, Silber** |

## Σημείωση χρήσης

Doppelwandiges Abflußrohr, DN 40 - DN 150 bestend aus: Innenrohr aus LORO-X Stahlabflußrohr, PU-Däammschicht Baustoffklasse B2, FCKW-frei. Außenrohr aus LORO-X Stahlabflußrohr

## Λήψεις

Οδηγίες εγκατάστασης (PDF) Φυλλάδιο (PDF) BIM IFC4 (parametrisch)

Alles online