LORO-X COMPOSITE BEND 87 DEGREE DN 32

LORO-Composite Pipe Bend 87 degrees DN 32

Text pro výběrové řízení

LORO-X compound pipe bend consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized), 87 degrees, DN32

Údaje o artiklu

EAN kód	**4038088072158**
ETIM třída	**EC003024**
Jmenovitý průměr	**DN 32**
Jmenovitá délka/stupeň	**87**
Vnější rozměry (VxŠxD)	**89 x 142 x 149 mm**
Hmotnost	**0,80 Kg (STK)**
Skupina produktů	**3**
Celní sazebník	**73089098**
Materiál / Barva	**Stahl feuerverzinkt, Silber**

Pokyny k použití

Doppelwandiges Abflußrohr, DN 40 - DN 150 bestend aus: Innenrohr aus LORO-X Stahlabflußrohr, PU-Däammschicht Baustoffklasse B2, FCKW-frei. Außenrohr aus LORO-X Stahlabflußrohr

Ke stažení

Alles online

Návod k instalaci (PDF) Prospekt (PDF) BIM IFC4 (parametrisch)