

LORO-X COMPOSITE BEND 87 DEGREE DN 32

LORO-Composite Pipe Bend 87 degrees DN 32

Voce di capitolato

LORO-X compound pipe bend consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized), 87 degrees, DN32



Dati articolo

Codice EAN	4038088072158
Classe ETIM	EC003024
Diametro nominale	DN 32
Lunghezza/grado nominale	87
Misure esterne (AxLxP)	89 x 142 x 149 mm
Peso	0,80 Kg (STK)
Gruppo prodotti	3
Numero tariffa doganale	73089098
Materiale / Colore	Stahl feuerverzinkt, Silber

Note d'uso

Doppelwandiges Abflußrohr, DN 40 - DN 150 bestehend aus: Innenrohr aus LORO-X Stahlabflußrohr, PU-Dämmschicht Baustoffklasse B2, FCKW-frei. Außenrohr aus LORO-X Stahlabflußrohr

Download



Alles online

[Istruzioni di installazione \(PDF\)](#)

[Brochure \(PDF\)](#)

[BIM IFC4 \(parametric\)](#)