

LORO-X COMPOSITE BEND 87 DEGREE DN 40

LORO-Composite Pipe Bend 87 degrees DN 40

Popis

LORO-X compound pipe bend consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized), 87 degrees, DN40




Údaje o artikli

EAN kód	4038088049945
ETIM trieda	EC003024
Menovitý priemer	DN 40
Menovitá dĺžka/stupeň	87
Vonkajšie rozmery (VxŠxH)	89 x 169 x 173 mm
Hmotnosť	1,20 Kg (STK)
Skupina produktov	3
Colný sadzobník	73089098
Materiál / Farba	Stahl feuerverzinkt, Silber

Pokyny na použitie

Doppelwandiges Abflußrohr, DN 40 - DN 150 bestehend aus: Innenrohr aus LORO-X Stahlabflußrohr, PU-Dämmschicht Baustoffklasse B2, FCKW-frei. Außenrohr aus LORO-X Stahlabflußrohr



Na stiahnutie



Alles online

[Návod na montáž \(PDF\)](#)
[CAD 2D \(DXF\)](#)

[Rozmerový výkres \(PDF\)](#)
[CAD \(DWG\)](#)

[Prospekt \(PDF\)](#)
[BIM IFC4 \(parametrisch\)](#)