LORO-X COMPOSITE BEND 70 DEGREE DN 40

LORO-Composite Pipe Bend 70 degrees DN 40

Beskrivningstext

LORO-X compound pipe bend consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized), 70 degrees, DN40

Artikeldata

EAN-kod	4038088086452
ETIM-klass	EC003024
Nominell diameter	DN 40
Nominell längd/grad	70
Yttermått (HxBxL)	89 x 180 x 160 mm
Vikt	1,10 Kg (STK)
Produktgrupp	3
Tullnummer	73089098
Material / Färg	Stahl feuerverzinkt, Silber

Användningsanvisning

Doppelwandiges Abflußrohr, DN 40 - DN 150 bestend aus: Innenrohr aus LORO-X Stahlabflußrohr, PU-Däammschicht Baustoffklasse B2, FCKW-frei. Außenrohr aus LORO-X Stahlabflußrohr

Nedladdningar

Monteringsanvisning (PDF)

Broschyr (PDF)

BIM IFC4 (parametrisch)

Alles online