

LORO-X COMPOSITE BEND 70 DEGREE DN 40

LORO-Composite Pipe Bend 70 degrees DN 40

Text pentru caietul de sarcini

LORO-X compound pipe bend consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized), 70 degrees, DN40



Date articol

Cod EAN	4038088086452
Clasă ETIM	EC003024
Diametru nominal	DN 40
Lungime/grad nominal	70
Dimensiuni exterioare (ÎxLxA)	89 x 180 x 160 mm
Greutate	1,10 Kg (STK)
Grupă de produse	3
Număr tarif vamal	73089098
Material / Culoare	Stahl feuerverzinkt, Silber

Notă de utilizare

Doppelwandiges Abflußrohr, DN 40 - DN 150 bestehend aus: Innenrohr aus LORO-X Stahlabflußrohr, PU-Dämmschicht Baustoffklasse B2, FCKW-frei. Außenrohr aus LORO-X Stahlabflußrohr

Descărcări



Alles online

[Instrucțiuni de montaj \(PDF\)](#)

[Broșură \(PDF\)](#)

[BIM IFC4 \(parametric\)](#)