

## LORO-X COMPOSITE BEND 70 DEGREE DN 40

### LORO-Composite Pipe Bend 70 degrees DN 40

#### Beskrivelsestekst

LORO-X compound pipe bend consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized), 70 degrees, DN40



#### Artikkeldata

|                       |                             |
|-----------------------|-----------------------------|
| EAN-kode              | 4038088086452               |
| ETIM-klasse           | EC003024                    |
| Nominell diameter     | DN 40                       |
| Nominell lengde/grad  | 70                          |
| Utvendige mål (HxBxL) | 89 x 180 x 160 mm           |
| Vekt                  | 1,10 Kg (STK)               |
| Produktgruppe         | 3                           |
| Tolltariffnummer      | 73089098                    |
| Materiale / Farge     | Stahl feuerverzinkt, Silber |

#### Bruksanvisning

Doppelwandiges Abflußrohr, DN 40 - DN 150 bestend aus: Innenrohr aus LORO-X Stahlabflußrohr, PU-Dämmschicht Baustoffklasse B2, FCKW-frei. Außenrohr aus LORO-X Stahlabflußrohr

#### Nedlastinger



Alles online

[Monteringsanvisning \(PDF\)](#)
[Brosjyre \(PDF\)](#)
[BIM IFC4 \(parametrisk\)](#)