LORO-X COMPOSITE BEND 45 DEGREE DN 32

LORO-Composite Pipe Elbow 45 degrees DN 32

Texte de prescription

LORO-X compound pipe bend consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized), 45 degrees, DN32



Données de l'article

Code EAN	**4038088072165**
Classe ETIM	**EC003024**
Diamètre nominal	**DN 32**
Longueur/degré nominal	**45**
Dimensions extérieures (HxLxP)	**89 x 125 x 156 mm**
Poids	**0,60 Kg (STK)**
Groupe de produits	**3**
Numéro tarifaire douanier	**73089098**
Matériau / Couleur	**Stahl feuerverzinkt, Silber**

Note d'utilisation

Doppelwandiges Abflußrohr, DN 40 - DN 150 bestend aus: Innenrohr aus LORO-X Stahlabflußrohr, PU-Däammschicht Baustoffklasse B2, FCKW-frei. Außenrohr aus LORO-X Stahlabflußrohr

Téléchargements

Alles online

Notice d'installation (PDF)
Dessin dimensionnel (PDF)
Brochure (PDF)
CAD 2D (DXF)
CAD (DWG)
BIM IFC4 (parametrisch)