LORO-X COMPOSITE BEND 45 DEGREE DN 150

LORO-Composite Pipe Elbow 45 degrees DN 150

Description

LORO-X compound pipe bend consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized), 45 degrees, DN150



Article information

EAN Code	**4038088025178**
ETIM Class	**EC003024**
Nominal diameter	**DN 150**
Nominal length/degree	**45**
Outside measurements (HxWxL)	**219 x 297 x 352 mm**
Weight	**8,00 Kg (STK)**
Product group	**3**
Customs tariff number	**73089098**
Material / Color	**Stahl feuerverzinkt, Silber**

Usage note

Doppelwandiges Abflußrohr, DN 40 - DN 150 bestend aus: Innenrohr aus LORO-X Stahlabflußrohr, PU-Däammschicht Baustoffklasse B2, FCKW-frei. Außenrohr aus LORO-X Stahlabflußrohr

Downloads

Alles online

Installation (PDF)
CAD 2D (DXF)
CAD drawing (PDF)
CAD (DWG)
Brochure (PDF)
BIM IFC4 (parametrisch)