LORO-VERBUNDROHR BOGEN 30 GR.DN 32

LORO-Composite Pipe Bend 30 degrees DN 32

Bestektekst

LORO-X compound pipe bend consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized), 30 degrees, DN32



Artikelgegevens

EAN-code	**4038088094242**
ETIM Klasse	**EC003024**
Nominale diameter	**DN 32**
Nominale lengte/graad	**30**
Buitenafmetingen (HxBxL)	**89 x 125 x 155 mm**
Gewicht	**0,50 Kg (STK)**
Productgroep	**3**
Douanetariefnummer	**73089098**
Materiaal / Kleur	**Stahl feuerverzinkt, Silber**

Gebruiksaanwijzing

Doppelwandiges Abflußrohr, DN 40 - DN 150 bestend aus: Innenrohr aus LORO-X Stahlabflußrohr, PU-Däammschicht Baustoffklasse B2, FCKW-frei. Außenrohr aus LORO-X Stahlabflußrohr

Downloads

Alles online

Installatiehandleiding (PDF)
CAD 2D (DXF)
BIM IFC4 (parametrisch)
Maattekening (PDF)
CAD 3D (DWG)
BIM 3D (IFC)
Brochure (PDF)
BIM 3D (STEP)