LORO-X COMPOSITE BEND 15 DEGREE DN 100

LORO-Composite Pipe bend 15 degrees DN 100

Beskrivning

LORO-X compound pipe bend consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized), 15 degrees, DN100



Artikeldata

EAN-kod	**4038088025253**
ETIM-klass	**EC003024**
Nominell diameter	**DN 100**
Nominell längd/grad	**15**
Yttermått (HxBxL)	**133 x 158 x 222 mm**
Vikt	**2,66 Kg (STK)**
Produktgrupp	**3**
Tullnummer	**73089098**
Material / Färg	**Stahl feuerverzinkt, Silber**

Användningsanvisning

Doppelwandiges Abflußrohr, DN 40 - DN 150 bestend aus: Innenrohr aus LORO-X Stahlabflußrohr, PU-Däammschicht Baustoffklasse B2, FCKW-frei. Außenrohr aus LORO-X Stahlabflußrohr

Nedladdningar

Alles online

Monteringsanvisning (PDF)
Måttritning (PDF)
Broschyr (PDF)
CAD 2D (DXF)
CAD (DWG)
BIM IFC4 (parametrisch)