

LORO-X COMPOSITE BEND 15 DEGREE DN 125

LORO-Composite Pipe bend 15 degrees DN 125

Descrição

LORO-X compound pipe bend consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized), 15 degrees, DN125




Dados do artigo

Código EAN	4038088025260
Classe ETIM	EC003024
Diâmetro nominal	DN 125
Comprimento/grau nominal	15
Medidas exteriores (AxLxP)	168 x 194 x 242 mm
Peso	5,00 Kg (STK)
Grupo de produtos	3
Número de pauta aduaneira	73089098
Material / Cor	Stahl feuerverzinkt, Silber

Nota de utilização

Doppelwandiges Abflußrohr, DN 40 - DN 150 bestehend aus: Innenrohr aus LORO-X Stahlabflußrohr, PU-Dämmschicht Baustoffklasse B2, FCKW-frei. Außenrohr aus LORO-X Stahlabflußrohr



Transferências



Alles online

[Instruções de instalação \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[Desenho cotado \(PDF\)](#)

[CAD \(DWG\)](#)

[Brochura \(PDF\)](#)

[BIM IFC4 \(paramétrisch\)](#)