


LORO-X COMPOSITE CONNECTING BEND FOR SIPHONIC FLOW 90 DEGREE DN 70/70

LORO multilayer pipe connection bend DN 70/70

Beschrijving

LORO-DRAINJET compound pipe connecting bend consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized), 90 degrees, DN70/70



Artikelgegevens

EAN-code	4038088067055
ETIM Klasse	EC003024
Nominale diameter	DN 70, DN 70
Nominale lengte/graad	90
Buitenafmetingen (HxBxL)	102 x 191 x 551 mm
Gewicht	6,00 Kg (STK)
Productgroep	3
Douanetariefnumme	73089098
r	
Materiaal / Kleur	Stahl feuerverzinkt, Silber

Gebruiksaanwijzing

kein Verwendungshinweis notwendig

Downloads



Alles online

[Installatiehandleiding \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[BIM IFC4 \(parametrisch\)](#)

[Maattekening \(PDF\)](#)

[CAD 3D \(DWG\)](#)

[BIM 3D \(IFC\)](#)

[Brochure \(PDF\)](#)

[BIM 3D \(STEP\)](#)