

LORO-X COMPOSITE CONNECTING PIPE FOR SIPHONIC FLOW DN 70/50

LORO multilayer pipe connection piece DN 70/50

Descripción

LORO-DRAINJET compound pipe connector consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized), DN70/50




Datos del artículo

Código EAN	4038088067390
Clase ETIM	EC003024
Diámetro nominal	DN 70, DN 50
Medidas exteriores (AxAxL)	102 x 102 x 305 mm
Peso	2,15 Kg (STK)
Grupo de productos	3
Número de arancel aduanero	73089098
Material / Color	Stahl feuerverzinkt, Silber

Nota de uso

kein Verwendungshinweis notwendig



Descargas



Alles online

[Instrucciones de instalación \(PDF\)](#)
[CAD 2D \(DXF\)](#)

[Dibujo dimensional \(PDF\)](#)
[CAD \(DWG\)](#)

[Folleto \(PDF\)](#)