

LORO-X COMPOSITE PIPE WITH CLEANOUT DN 80

LORO multilayer pipe with cleaning opening 500 mm DN 80

Beskrivningstext

LORO-X compound pipe with clean-out opening (projecting), consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized), 500 mm, DN 80




Artikeldata

EAN-kod	4038088086438
ETIM-klass	EC010323
Nominell diameter	DN 80
Nominell längd/grad	500
Yttermått (HxBxL)	181 x 133 x 575 mm
Vikt	7,60 Kg (STK)
Produktgrupp	3
Tullnummer	73063012
Material / Färg	Stahl feuerverzinkt, Silber

Användningsanvisning

kein Verwendungshinweis notwendig



Nedladdningar



Alles online

[Monteringsanvisning \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[Måttritning \(PDF\)](#)

[CAD \(DWG\)](#)

[Broschyr \(PDF\)](#)