

LORO-X COMPOSITE PIPE WITH CLEANOUT DN 150

LORO multilayer pipe with cleaning opening 500 mm DN 150

Kuvaus

LORO-X compound pipe with clean-out opening (projecting), consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized), 500 mm, DN150




Tuotetiedot

EAN-koodi	4038088025321
ETIM-luokka	EC010323
Nimellishalkaisija	DN 150
Nimellispituus/-aste	500
Ulkomitat (KxLxS)	301 x 219 x 580 mm
Paino	17,00 Kg (STK)
Tuoteryhmä	3
Tullitariffin numero	73063018
Materiaali / Väri	Stahl feuerverzinkt, Silber

Käyttöohje

kein Verwendungshinweis notwendig



Lataukset



Alles online

[Asennusohje \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[BIM 3D \(IFC\)](#)

[Mittapiirustus \(PDF\)](#)

[CAD 3D \(DWG\)](#)

[Esite \(PDF\)](#)

[BIM 3D \(STEP\)](#)