


LORO-X COMPOSITE PIPE WITH CLEANOUT DN 150

LORO multilayer pipe with cleaning opening 500 mm DN 150

Beschrijving

LORO-X compound pipe with clean-out opening (projecting), consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized), 500 mm, DN150



Artikelgegevens

EAN-code	4038088025321
ETIM Klasse	EC010323
Nominale diameter	DN 150
Nominale lengte/graad	500
Buitenafmetingen (HxBxL)	301 x 219 x 580 mm
Gewicht	17,00 Kg (STK)
Productgroep	3
Douanetariefnummer	73063018
Materiaal / Kleur	Stahl feuerverzinkt, Silber

Gebruiksaanwijzing

kein Verwendungshinweis notwendig

Downloads



Alles online

[Installatiehandleiding \(PDF\)](#)

CAD 2D (DXF)

BIM 3D (IFC)

[Maattekening \(PDF\)](#)

CAD 3D (DWG)

[Brochure \(PDF\)](#)

BIM 3D (STEP)