

LORO-X COMPOSITE PIPE WITH CLEANOUT DN 150

LORO multilayer pipe with cleaning opening 500 mm DN 150

Descripción

LORO-X compound pipe with clean-out opening (projecting), consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized), 500 mm, DN150




Datos del artículo

Código EAN	4038088025321
Clase ETIM	EC010323
Diámetro nominal	DN 150
Longitud/grado nominal	500
Medidas exteriores (AxAxL)	301 x 219 x 580 mm
Peso	17,00 Kg (STK)
Grupo de productos	3
Número de arancel aduanero	73063018
Material / Color	Stahl feuerverzinkt, Silber

Nota de uso

kein Verwendungshinweis notwendig



Descargas



Alles online

[Instrucciones de instalación \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[BIM 3D \(IFC\)](#)

[Dibujo dimensional \(PDF\)](#)

[CAD 3D \(DWG\)](#)

[Folleto \(PDF\)](#)

[BIM 3D \(STEP\)](#)